

• Collapsible, full-panelled end walls

• Can carry maximum payload in both positions

• End wall can be used as a ramp to a maximum of 3,000kg distributed load (option)

• Versatile multiple lashing zones around and across the base

• Domino type 4 hinge

• Both 20' and 40' fitted with fork pockets



• 20' and 40' domino type 4 flush-folding Flat Racks

• Robust, high-quality construction for low maintenance

• Flush-decked in both open and collapsed end wall positions

• Available for operational lease, term lease and sale



Both 20' and 40' models are the latest version of the well-proven and universal design by C.S.A.

End walls can be lowered for vehicle loading



7 high nest stacking for empty positioning of 20' Flat Racks and 4 high nest stacking of 40' Flat Racks

Typical specifications

Container type	20'	40'
External dimensions		
Length	6,058mm	12,192mm
Width	2,438mm	2,438mm
Height	2,591mm	2,591mm
Bed height	370mm	647mm
Internal dimensions		
Length between end panels	6,038mm	11,980mm
Side access	5,612mm	11,684mm
Length between headers	5,850mm	11,984mm
Supported width	2,210mm	2,378mm
Cargo width between corner posts	2,227mm	2,230mm
Cargo height	2,213mm	1,960mm
Folded height	370mm (7 units per 8' 6" bundle)	647mm (4 units per 8' 6" bundle)
Cubic capacity	29.3cu m	56.7cu m
Ratings		
Maximum gross weight	34,000kg	50,000kg
Tare weight	2,740kg	5,000kg
Payload	31,260kg	45,000kg
Concentrated load	20,000kg (over central 2 metres)	30,000kg (over central 3 metres)
Stacking	86,400kg/post	86,400kg/post
Lashings		
Stanchion sockets	5 per side	7 per side
Lashing bars	5,000kg pull	5,000kg pull